

**Specifications:****SAE:** 50**API:** CD

ASTM D-445	Viscosity@40C :	To be Reported
ASTM D-445	Viscosity@100C :	16.3-21.9
ASTM D-2270	Viscosity Index :	90 Min
ASTM D-92	Flash Point C :	220 Min
ASTM D-97	Pour Point :	-6 Max
ASTM D-2896	TBN :	7 Min
ASTM D-874	Sulfated Ash, %wt :	0.7 Min
ASTM D-1500	Color :	4 Max
ASTM D-1298	Specific Gravity @15.6C :	to be reported
ASTM D-130	Copper Strip Corrosion @100C for 3hrs:	1 Max

**ASTM:** American Society for Testing and Material**SAE:** Society of Automotive Engineers**API:** American Petroleum Institute

- **Description**

## Introduction

Mono-Grade Motor Oils for Tractors, Trucks, Buses and Stationary Diesel Engines Servo D3 oils are Economical motor-oils providing very good lubrication and heat-exchange for all diesel engines Designed for heavy-duty use.

## Applications

Suitable for Farm Tractors, Trucks, Buses and Stationary Diesel Engines mostly used in tough dusty environment

## **Performance, Benefits & Features**

All WELTA Diesel Engine Oils are blended with extra emulsifiers to ensure that the fine dust particles that make it through the filters stay suspended and do not harm the engine's friction parts i.e. Pistons, Piston-Rings, Cylinder-Liners, Main and Big-End Bearings, C-R Bushes and Cam Bushes Complete additive package addition ensures peak performance in hot weather Product is manufactured as per SAE and API specifications mentioned on the product

## **Health & Safety**

Extended exposure to skin could be hazardous. Wash hands after coming in contact. Keep away from eyes.

## **Protect Environment**

Take used oil to an authorized collection point. Do not discharge into drains, soil or water